

WT40XK2C



Packed with the power to transfer up to 1,640 litres (361 imp. gallons) per minute, this pump can even remove water containing rocks and debris up to 27 mm (1 1/16 inches) in diameter from a construction site. An easy access door for pump housing flushing comes standard.

Features

- Honda GX340 OHV engine
- 102 mm (4") suction and discharge ports
- Pumps 1,640 litres per minute (361 Imp. Gal. per minute)
- Oil Alert™ is standard
- Full frame

Specifications

Pump	Centrifugal
Type	Self-priming
Suction Port Diameter	102 mm /4 in.
Discharge Port Diameter	102 mm /4 in.
Litres per minute	1640
Imp. gal. per minute	361
Litres per hour	98400
Imp. gal. per hour	21660
Total Head	26 m /85 ft.
Suction Head (Total Lift)	8 m /26 ft.
Priming Time @ 5m(16.4 ft.)	160 seconds
Pump Body	Aluminum
Impeller	conical cast iron
Honda Engine	GX340K1 4-stroke
Type	OHV, air-cooled, single cyl.
Displacement	337 cc
Lubrication System	Splash type
Governor	Mechanical
Starting System	Recoil
Fuel Tank Capacity	6.5 L /1.43 Imp. gal.
Oil Alert	Standard
Drive Unit Type	Direct couple / mech. seal
Frame Type	Full Frame
Length	735 mm /28.9 in.
Width	535 mm /21.1 in.
Height	565 mm /22.2 in.
Dry Weight	78 kg. /172 lb.